

impression





impression

- INSPIRED BY STONES FROM THE MEDITERRANEAN AREA
- MULTIPLE COLORS, SHADE VARIATION AND VEINING
- UNEVEN TEXTURE ON THE SURFACE TO PROVIDE A NATURAL EFFECT
- GREAT VERSATILITY FOR DIFFERENT INTERIOR DESIGN STYLES



MEDITERRANEAN

UP-TO-DATE LOOK

The Impression Collection interprets the essence of precious marble quarried in the Mediterranean area, formed through a metamorphic process of sedimentary stones. The sinuous graphics of the surface, its multiple colors, impressive shade variations and veining allow great versatility for many interior design styles. Impression is suitable for multiple applications from wall to floor.

impression

Colors



WHITE



GRAY



TAUPE

Shade variation




WHITE



GRAY

COLORLED BODY PORCELAIN TILE



TAUPE



impression

Impression White 11^{3/4}"x23^{5/8}" - 30x60 cm
Impression White Leaf Mosaic 14^{1/2}"x8^{5/8}" - 37x22 cm
Impression White Bullnose 3"x24" - 7.2x60cm

impression



i m p r e s s i o n
Impression White Leaf Mosaic 14^{1/2}"x8^{5/8}" - 37x22 cm

i m p r e s s i o n
Impression Taupe 23^{5/8}"x47^{1/4}" - 60x120 cm
Impression White 23^{5/8}"x47^{1/4}" - 60x120 cm
Impression Taupe Cove Base 6"x12" - 15x30 cm





i m p r e s s i o n
Impression Taupe 23⁵/₈"x47¹/₄" - 60x120 cm
Impression White 23⁵/₈"x47¹/₄" - 60x120 cm
Impression Taupe Cove Base 6"x12" - 15x30 cm



impression

- Impression Gray 11³/₄" x 23⁵/₈" - 30x60 cm
- Impression White Mosaic 11³/₄" x 11³/₄" - 30x30 cm
- Impression White Leaf Mosaic 14¹/₂" x 8⁵/₈" - 37x22 cm
- Impression Gray Leaf Mosaic 14¹/₂" x 8⁵/₈" - 37x22 cm
- Impression Gray Bullnose 3" x 24" - 7.2x60 cm

i m p r e s s i o n
Impression Gray 11³/₄"x23⁵/₈" - 30x60 cm
Impression White Mosaic 11³/₄"x11³/₄" - 30x30 cm
Impression White Leaf Mosaic 14¹/₂"x8⁵/₈" - 37x22 cm



i m p r e s s i o n
Impression White Mosaic 11³/₄"x11³/₄" - 30x30 cm
Impression Gray Leaf Mosaic 14¹/₂"x8⁵/₈" - 37x22 cm



V4 SUBSTANTIAL VARIATION



Compliant with standards ANSI A137.1-2012

SIZE
11 3/4" x 23 5/8" - 30 x 60 cm
23 5/8" x 47 1/4" - 60 x 120 cm

THICKNESS
9 mm

FINISH
MATTE



IMPRESSION WHITE
11 3/4" x 23 5/8" - 30x60 cm
610010002800



IMPRESSION GRAY
11 3/4" x 23 5/8" - 30x60 cm
610010002801



IMPRESSION TAUPE
11 3/4" x 23 5/8" - 30x60 cm
610010002802



IMPRESSION WHITE
23 5/8" x 47 1/4" - 60x120 cm
610010002803



IMPRESSION GRAY
23 5/8" x 47 1/4" - 60x120 cm
610010002804



IMPRESSION TAUPE
23 5/8" x 47 1/4" - 60x120 cm
610010002805

MOSAICS & DECORS



IMPRESSION WHITE MOSAIC
11 3/4" x 11 3/4" - 30x30 cm
(Mosaic 2"x2")
610110000525




IMPRESSION GRAY MOSAIC
11 3/4" x 11 3/4" - 30x30 cm
(Mosaic 2"x2")
610110000526



IMPRESSION TAUPE MOSAIC
11 3/4" x 11 3/4" - 30x30 cm
(Mosaic 2"x2")
610110000527



IMPRESSION WHITE LEAF MOSAIC
14 1/2" x 8 5/8" - 37x22 cm
(Mosaic 2 3/8" x 6")
610110000536




IMPRESSION GRAY LEAF MOSAIC
14 1/2" x 8 5/8" - 37x22 cm
(Mosaic 2 3/8" x 6")
610110000537




IMPRESSION TAUPE LEAF MOSAIC
14 1/2" x 8 5/8" - 37x22 cm
(Mosaic 2 3/8" x 6")
610110000538

COORDINATING TRIMS

		Bullnose	Cove base
	IMPRESSION WHITE	610130004800	610130004811
	IMPRESSION GRAY	610130004801	610130004812
	IMPRESSION TAUPE	610130004802	610130004813



Bullnose
3" x 24" - 7.2x60 cm



Cove base
6" x 12" - 15x30 cm - 8.5mm



Compliant with standards ANSI A137.1-2012



SIZE

11 3/4" x 23 5/8" - 30 x 60 cm
23 5/8" x 47 1/4" - 60 x 120 cm

THICKNESS

9 mm

FINISH

matte



V4 SUBSTANTIAL VARIATION

Random color and/or texture differences from tile to tile, so that one tile may have totally different colors and/or texture from that on other tiles. Thus, the final installation will be unique. It is recommended that the range be viewed before selection.

FIELD TILES

Available in all colors

Commercial size (in)	Nominal size (in)	Thickness (mm)	Finish	Rectified edge
12" x 24"	11 3/4" x 23 5/8"	9 mm	Matte	-
24" x 48"	23 5/8" x 47 1/4"	9 mm	Matte	Yes

MOSAICS

AND COORDINATING TRIMS

Available in all colors

Commercial size (in)	Nominal size (in)	Thickness (mm)	Finish
Mosaic 2" x 2"	11 3/4" x 11 3/4"	9 mm	Matte
Leaf Mosaic 2 3/8" x 6"	14 1/2" x 8 5/8"	9 mm	Matte
Bullnose 3" x 24"	2 7/8" x 23 5/8"	9 mm	Matte
Cove Base 6" x 12"	5 7/8" x 11 3/4"	8.5 mm (*)	Matte

Please refer to caliber chart for work sizes. Close joints are not recommended. (*): Cove Base thickness is 7 mm on flat top part.

PERFORMANCE & FEATURES

REGULARITY CHARACTERISTICS



Nominal Size	ASTM C499	-3.00%	3.00%	-3.00%	2.00%	Compliant
Caliber Range (Variation from average facial dimension of sample)		-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant
Thickness ⁽¹⁾		N/A	Range: 0.40 in (1.02 mm)	N/A	Range: 0.40 in (1.02 mm)	Compliant
Wedging	ASTM C502	-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant
Warpage Edge	ASTM C485	-0.75% or -0.09 in (-2.3 mm) (*)	0.75% or 0.09 in (2.3 mm) (*)	-0.40% or -0.05 in (-1.3 mm) ⁽²⁾ or -1.8 mm ⁽³⁾ (*)	0.40% or 0.05 in (1.3 mm) ⁽²⁾ or 1.8 mm ⁽³⁾ (*)	Compliant
Warpage Diagonal		-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (*)	-0.40% or -0.07 in (-1.8 mm) (*)	0.40% or 0.07 in (1.8 mm) (*)	Compliant

STRUCTURAL CHARACTERISTICS



Water Absorption	ASTM C373	≤ 0.5%	≤ 0.5%
------------------	-----------	--------	--------

BULK MECHANICAL CHARACTERISTICS



Breaking Strength	ASTM C648	Average ≥ 250 lbf. (1.11 kN) Individual ≥ 225 lbf. (1.00 kN)	≥ 350 lbf. avg
-------------------	-----------	---	----------------

PHYSICAL PROPERTIES



Bond Strength	ASTM C482	≥ 50 psi (0.34 Mpa)	≥ 100 psi
---------------	-----------	---------------------	-----------

THERMAL AND IGROMETRIC CHARACTERISTICS



Resistance to Freeze/Thaw Cycling	ASTM C1026	As Reported	Resistant
-----------------------------------	------------	-------------	-----------

CHEMICAL CHARACTERISTICS



Chemical Resistance	ASTM C650	As Reported	Unaffected
---------------------	-----------	-------------	------------



Stain Resistance	ASTM C1378	As Reported	Unaffected
------------------	------------	-------------	------------

SAFETY CHARACTERISTICS



Dynamic coefficient of friction	DCOF	Requires a minimum value of 0.42 for commercial areas that are likely to be wet	> 0.42 Wet
---------------------------------	------	---	------------

(*) Whichever is less

(1) May not apply to textured surfaces or tiles with uneven back patterns.

(2) Whichever is less, for tiles up to 24"x24" (610 mm x 610 mm).

(3) Applies to tiles larger than 24"x24" (610 mm x 610 mm).

For more details please see the catalogue or visit atlasconcordeusa.com
The Health Product Declaration® logo is a registered trademark of HPD Collaborative.

